



Cu/PVC/Bd/Lsh/Bd/SWA/PVC

IEC 60502

Description:

Wire armoured control cable, lead sheathed
 with copper conductor & PVC insulation.
 For controlling, operating and signalling.

Number of Cores & Cross Selection mm ²	Insulation Thickness PH mm	Lead Thickness mm	Diameter of Armour mm	Sheath Thickness mm	Cable Diameter Approx. mm	Total Weight Approx. kg/km
5 x2.5 RM	0.8	1.2	1.25	1.8	23.3	1498
7 x2.5 RM	0.8	1.2	1.6	1.8	25.3	1787
8 x2.5 RM	0.8	1.2	1.6	1.8	27.0	1971
10 x2.5 RM	0.8	1.2	1.6	1.8	29.0	2223
12 x2.5 RM	0.8	1.2	1.6	1.8	29.9	2346
16 x2.5 RM	0.8	1.2	2.0	1.9	33.0	2902
18 x2.5 RM	0.8	1.2	2.0	1.9	34.1	3060
20 x2.5 RM	0.8	1.3	2.0	2.0	35.7	3381
24 x2.5 RM	0.8	1.3	2.0	2.1	38.0	3810
30 x2.5 RM	0.8	1.4	2.0	2.1	40.4	4259
40 x2.5 RM	0.8	1.5	2.0	2.2	44.7	5138
61 x2.5 RM	0.8	1.6	2.5	2.5	53.5	7314

1-Solid or Stranded Circular Conductor 2-PVC Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Lead Sheath 5-Extruded PVC Bedding 6-Galvanized Steel Wire Armour 7-PVC Sheathing.

Maximum conductor temperature: 70°C

Conductor cross-section of 1 and 1.5 mm² are also available.