



Cu/PVC/Bd/CuB/Pet/PVC

IEC 60502

**Description:**

control cable with braided screen, copper conductor & PVC insulation.

For controlling, operating and signalling.

<i>Number of Cores &amp; Cross Selection mm<sup>2</sup></i>	<i>Insulation Thickness mm</i>	<i>Sheath Thickness mm</i>	<i>Cable Diameter Approx. mm</i>	<i>Total Weight Approx. kg/km</i>
5 x2.5 RM	0.8	1.8	17.3	437
7 x2.5 RM	0.8	1.8	18.5	495
8 x2.5 RM	0.8	1.8	20.3	557
10 x2.5 RM	0.8	1.8	22.6	683
12 x2.5 RM	0.8	1.8	23.3	767
16 x2.5 RM	0.8	1.8	25.3	934
18 x2.5 RM	0.8	1.8	26.4	1013
20 x2.5 RM	0.8	1.8	27.6	1110
24 x2.5 RM	0.8	1.8	30.3	1289
30 x2.5 RM	0.8	1.8	31.8	1503
40 x2.5 RM	0.8	1.9	35.6	1920
61 x2.5 RM	0.8	2.1	42.9	2848

1-Stranded Circular or Solid Conductor 2-PVC Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Copper Braided Screen 5-Polyester Tape 6-PVC Sheathing.

**Maximum conductor temperature: 70°C**

Conductor cross-section of 1 and 1.5 mm<sup>2</sup> are also available.