



TiCu/PVC/Bd/TCB/Pet/PVC

IEC 60502

Description :

control cable with tinned copper braided screen,
tinned copper conductor & PVC insulation.
For controlling, operating and signalling.

Number of Cores & Cross Selection mm²	Insulation Thickness mm	Sheath Thickness mm	Cable Diameter Approx. mm	Total Weight Approx. kg/km
5 x2.5 RM	0.8	1.8	17.3	446
7 x2.5 RM	0.8	1.8	18.5	505
8 x2.5 RM	0.8	1.8	20.3	569
10 x2.5 RM	0.8	1.8	22.6	697
12 x2.5 RM	0.8	1.8	23.3	783
16 x2.5 RM	0.8	1.8	25.3	953
18 x2.5 RM	0.8	1.8	26.4	1034
20 x2.5 RM	0.8	1.8	27.6	1133
24 x2.5 RM	0.8	1.8	30.3	1316
30 x2.5 RM	0.8	1.8	31.8	1533
40 x2.5 RM	0.8	1.9	35.6	1960
61 x2.5 RM	0.8	2.1	42.9	2904

1-Stranded Circular or Solid Conductor 2-PVC Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Tinned Copper Braided Screen 5-Polyester Tape 6-PVC Sheathing.

Maximum conductor temperature: 70°C

Conductor cross-section of 1 and 1.5 mm² are also available.