



Cu/PVC/Bd/DTA/PVC

IEC 60502

Description :

Tape armoured control cable with copper conductor & PVC insulation.
For controlling, operating and signalling.

Number of Cores & Cross Selection mm²	Insulation Thickness mm	Tape Armour Thickness mm	Sheath Thickness mm	Cable Diameter Approx. mm	Total Weight Approx. kg/km
8 x2.5 RM	0.8	0.2	1.8	20.7	629
10 x2.5 RM	0.8	0.2	1.8	22.7	740
12 x2.5 RM	0.8	0.2	1.8	23.4	820
16 x2.5 RM	0.8	0.2	1.8	25.4	995
18 x2.5 RM	0.8	0.2	1.8	26.5	1085
20 x2.5 RM	0.8	0.2	1.8	27.7	1177
24 x2.5 RM	0.8	0.2	1.8	30.4	1364
30 x2.5 RM	0.8	0.2	1.8	31.9	1592
40 x2.5 RM	0.8	0.2	1.9	35.7	2011
61 x2.5 RM	0.8	0.5	2.2	44.1	3182

1-Stranded Circular Conductor 2-PVC Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Galvanized Steel Tape Armour 5-PVC Sheathing.

Maximum conductor temperature: 70°C

Conductor cross-section of 1 and 1.5 mm² are also available.