



Cu/XLPE/Bd/CWS/PVC

IEC 60502

Description :

Screened control cable, with copper conductor & XLPE insulation.

For controlling, operating and signalling.

<i>Number of Cores & Cross Selection mm²</i>	<i>Insulation Thickness mm</i>	<i>Sheath Thickness mm</i>	<i>Cable Diameter Approx. mm</i>	<i>Total Weight Approx. kg/km</i>
5 x2.5 / 2.5 RM	0.7	1.8	17.1	382
7 x2.5 / 2.5 RM	0.7	1.8	18.2	429
8 x2.5 / 4 RM	0.7	1.8	19.9	481
10 x2.5 / 4 RM	0.7	1.8	21.8	567
12 x2.5 / 4 RM	0.7	1.8	22.4	632
16 x2.5 / 6 RM	0.7	1.8	24.3	786
18 x2.5 / 6 RM	0.7	1.8	25.4	858
20 x2.5 / 10 RM	0.7	1.8	26.6	967
24 x2.5 / 10 RM	0.7	1.8	28.9	1112
30 x2.5 / 10 RM	0.7	1.8	30.5	1302
40 x2.5 / 10 RM	0.7	1.9	34.2	1648
61 x2.5 / 10 RM	0.7	2.1	40.9	2401

1-Stranded Circular or Solid Conductor 2-XLPE Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Copper Wire Screen 5-PVC Sheathing.

Maximum conductor temperature: 90°C

Conductor cross-section of 1 and 1.5 mm² are also available.