


**Cu/XLPE/Bd/CuB/Pet/PVC**
**IEC 60502**
**Description:**

control cable with braided screen, copper conductor &amp; XPLE insulation.

For controlling, operating and signalling.

<i>Number of Cores &amp; Cross Selection mm<sup>2</sup></i>	<i>Insulation Thickness mm</i>	<i>Sheath Thickness mm</i>	<i>Cable Diameter Approx. mm</i>	<i>Total Weight Approx. kg/km</i>
5 x2.5 RM	0.7	1.8	16.8	412
7 x2.5 RM	0.7	1.8	17.9	456
8 x2.5 RM	0.7	1.8	19.6	520
10 x2.5 RM	0.7	1.8	21.5	610
12 x2.5 RM	0.7	1.8	22.1	675
16 x2.5 RM	0.7	1.8	24.3	853
18 x2.5 RM	0.7	1.8	25.4	935
20 x2.5 RM	0.7	1.8	26.6	1009
24 x2.5 RM	0.7	1.8	28.9	1170
30 x2.5 RM	0.7	1.8	30.5	1376
40 x2.5 RM	0.7	1.9	34.2	1739
61 x2.5 RM	0.7	2.1	41.1	2574

1-Stranded Circular or Solid Conductor 2-XLPE Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Copper Braided Screen 5-Polyester Tape 6-PVC Sheathing.

**Maximum conductor temperature: 90°C**

 Conductor cross-section of 1 and 1.5 mm<sup>2</sup> are also available.