



TiCu/XLPE/Bd/TCB/Pet/PVC

IEC 60502

Description :

control cable with tinned copper braided screen,
tinned copper conductor & XLPE insulation.
For controlling, operating and signalling.

Number of Cores & Cross Selection mm²	Insulation Thickness mm	Sheath Thickness mm	Cable Diameter Approx. mm	Total Weight Approx. kg/km
5 x2.5 RM	0.7	1.8	16.8	420
7 x2.5 RM	0.7	1.8	17.9	465
8 x2.5 RM	0.7	1.8	19.6	531
10 x2.5 RM	0.7	1.8	21.5	623
12 x2.5 RM	0.7	1.8	22.1	690
16 x2.5 RM	0.7	1.8	24.3	871
18 x2.5 RM	0.7	1.8	25.4	956
20 x2.5 RM	0.7	1.8	26.6	1031
24 x2.5 RM	0.7	1.8	28.9	1196
30 x2.5 RM	0.7	1.8	20.5	1407
40 x2.5 RM	0.7	1.9	34.2	1778
61 x2.5 RM	0.7	2.1	41.1	2629

1-Stranded Circular or Solid Conductor 2-XLPE Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Tinned Copper Braided Screen 5-Polyester Tape 6-PVC Sheathing.

Maximum conductor temperature: 90°C

Conductor cross-section of 1 and 1.5 mm² are also available.