



Cu/XLPE/Bd/DTA/PVC

IEC 60502

Description :

Tape armoured control cable with copper conductor & XLPE insulation.

For controlling, operating and signalling.

<i>Number of Cores & Cross Selection mm²</i>	<i>Insulation Thickness mm</i>	<i>Tape Armour Thickness mm</i>	<i>Sheath Thickness mm</i>	<i>Cable Diameter Approx. mm</i>	<i>Total Weight Approx. kg/km</i>
10 x2.5 RM	0.7	0.2	1.8	21.9	686
12 x2.5 RM	0.7	0.2	1.8	22.5	757
16 x2.5 RM	0.7	0.2	1.8	24.4	915
18 x2.5 RM	0.7	0.2	1.8	25.5	997
20 x2.5 RM	0.7	0.2	1.8	26.7	1082
24 x2.5 RM	0.7	0.2	1.8	29.0	1250
30 x2.5 RM	0.7	0.2	1.8	30.6	1453
40 x2.5 RM	0.7	0.2	1.9	34.3	1832
61 x2.5 RM	0.7	0.2	2.1	41.0	2647

1-Stranded Circular Conductor 2-XLPE Insulation (Sequentially numbered for identification) 3-Extruded PVC Bedding 4-Galvanized Steel Tape Armour 5-PVC Sheathing.

Maximum conductor temperature: 90°C

Conductor cross-section of 1 and 1.5 mm² are also available.